

APC Service Bypass Panel- 230V; 100A; MBB; Hardwire input; (3) 30A Hardwire Output

SBP16KRMI4U

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Output Connector Type	Hard wire 3-wire (H N + E) 3
Number Of Rack Unit	4U
Number Of Cables	1
Provided Equipment	Installation guide Rack mounting brackets User manual

Physical

Colour	Black
Height	17.8 cm
Width	43.2 cm
Depth	67.3 cm
Net Weight	21.82 kg
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted

Input

Network Frequency	50/60 Hz
Number Of Input Connectors	1 hard wire 3-wire (H N + E) 1 hard wire 4-wire (3P + E)
Max Line Current	100 A
Input Current Limits	100 A
Load Capacity	20000 VA
Power Factor	01

Output

Max Current Draw	100 A
Protection Type	Circuit breaker

Efficiency 99 %

Conformance

Product Certifications	CSA GOST
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient Air Temperature For Operation	-2045 °C
Relative Humidity	095 %
Operating Altitude	015000 ft
Ambient Air Temperature For Storage	-4065 °C
Storage Relative Humidity	095 %
Storage Altitude	0.0015240.00 m

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	61 cm
Package 1 Length	99.1 cm
Package 1 Weight	31.753 kg
Unit Type Of Package 2	PAL
Number Of Units In Package 2	8
Package 2 Height	129.5 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	266.08 kg

Contractual warranty

Warranty 2 years (parts only)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more >

Well-being performance

