

Product datasheet

Specifications



Legacy Communications SmartSlot Card



AP9620

Overview

Presentation	UPS management SmartSlot Card which supports the UPSLink protocol for SMT, SMX and SURTD Smart-UPS.
Lead Time	Usually in Stock

Main

Provided Equipment	RS-232 configuration cable User manual
---------------------------	---

Physical

Colour	Black
Height	3.8 cm
Width	12.1 cm
Depth	11.4 cm
Net Weight	0.08 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Environmental

Ambient Air Temperature For Operation	0...45 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-5...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	23.5 cm
Package 1 Length	15.9 cm
Package 1 Weight	0.339 kg
Scc14	10731304283215

Contractual warranty

Warranty

2 years repair or replace

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more >](#)




Energy Efficient Take-back RoHS/REACH

Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
