

# Product datasheet

Specifications



## APC Back-UPS Pro, 1300VA/780W, Tower, 230V, 8x IEC C13 outlets, AVR, LCD, User Replaceable Battery

BR1300MI

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	230 V
Rated power in W	780 W
Rated power in VA	1300 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C13
Output connection type	6 IEC 60320 C13 2 IEC 60320 C13 surge
Battery type	Lead-acid battery

### Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Battery voltage	24 V
Battery capacity	6.0 Ah
Battery charger power	11 W rated
Battery power in VAh	177 VAh runtime
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC165</a>
Extended runtime	0

### General

Provided equipment	user manual USB cable
Number of power module free slots	0

---

Number of power module filled slots	0
-------------------------------------	---

---

Redundant	No
-----------	----

---

## Physical

---

Colour	Black
--------	-------

---

Height	10 cm
--------	-------

---

Width	25 cm
-------	-------

---

Depth	38.2 cm
-------	---------

---

Net weight	10.2 kg
------------	---------

---

Mounting preference	No preference
---------------------	---------------

---

Mounting mode	Not rack-mountable
---------------	--------------------

---

Two post mountable	0
--------------------	---

---

USB compatible	No
----------------	----

---

## Input

---

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

---

Input voltage limits	176...294 V
----------------------	-------------

---

Maximum input current	10 A
-----------------------	------

---

Switching current capacity	10 A
----------------------------	------

---

## Output

---

Maximum configurable power in W	780 W
---------------------------------	-------

---

Output frequency	50/60 Hz +/- 1 Hz sync to mains
------------------	---------------------------------

---

UPS type	Line interactive
----------	------------------

---

Maximum configurable power in VA	1300 VA
----------------------------------	---------

---

## Conformance

---

Product certifications	A-Tick C-Tick CE EAC RCM TISI
------------------------	--

---

Marking	GS Mark
---------	---------

---

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

---

## Environmental

---

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

---

Relative humidity	0...95 % non-condensing
-------------------	-------------------------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Ambient air temperature for storage	-15...45 °C
-------------------------------------	-------------

---

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

---

Storage altitude	0.00...15240.00 m
------------------	-------------------

---

Acoustic level	45 dBA
Heat dissipation	21.5 Btu/h

## Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rate	509 J
Noise suppression	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33 cm
Package 1 Width	22.5 cm
Package 1 Length	48.5 cm
Package 1 Weight	11.85 kg
SCC14	10731304346903

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	<a href="#">Yes</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

## Recommended replacement(s)