

# Product datasheet

Specifications



## APC Back-UPS, 500VA/300W, Tower, 230V, 4x IEC C13 Outlets , User Replaceable Battery

BK500EI

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	300 W
Rated power in VA	500 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
Output connection type	3 IEC 60320 C13 1 IEC 60320 C13 surge 2 IEC Jumpers surge
Number of cables	2
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD 1 x detachable IEC power cord 1 x detachable 1.2 m IEC power cord Telephone cable USB cable Warranty card

### Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	1
Battery voltage	12 V
Battery capacity	7.0 Ah
Battery charger power	10 W rated
Battery power in VAh	83 VAh capacity 84 VAh runtime
Battery life	4...6 year(s)
Replacement battery	<a href="#">RBC2</a>

Extended runtime	0
------------------	---

## General

Max runtime	45 min
-------------	--------

Number of power module free slots	0
-----------------------------------	---

Number of power module filled slots	0
-------------------------------------	---

Redundant	No
-----------	----

## Physical

Colour	Beige
--------	-------

Height	16.5 cm
--------	---------

Width	9.1 cm
-------	--------

Depth	28.4 cm
-------	---------

Net weight	6.32 kg
------------	---------

Mounting location	Front
-------------------	-------

Mounting preference	No preference
---------------------	---------------

Mounting mode	Not rack-mountable
---------------	--------------------

Two post mountable	0
--------------------	---

USB compatible	No
----------------	----

## Input

Network frequency	47...63 Hz 50/60 Hz +/- 3 Hz auto-sensing
-------------------	--

Input voltage limits	160...300 V adjustable 180...266 V
----------------------	---------------------------------------

Maximum input current	7 A
-----------------------	-----

Switching current capacity	7 A
----------------------------	-----

## Output

Maximum configurable power in W	300 W
---------------------------------	-------

Output frequency	47...63 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
------------------	--

UPS type	Standby
----------	---------

Wave type	Stepped approximation to a sinewave
-----------	-------------------------------------

Maximum configurable power in VA	500 VA
----------------------------------	--------

Transfer time	6 ms typical : 10 ms maximum
---------------	------------------------------

## Conformance

Product certifications	C-Tick CE GOST VDE
------------------------	-----------------------------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	40 dBA
Heat dissipation	24 Btu/h

## Communications & Management

Free slots	0
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rate	310 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.8 cm
Package 1 Width	24.1 cm
Package 1 Length	36.8 cm
Package 1 Weight	7.05 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	30
Package 2 Height	133 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	490 kg
SCC14	10731304016356

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

**Recommended replacement(s)**