

# Product datasheet

Specifications



## APC Symmetra LX 8kVA Scalable to 16kVA N+1 Tower, 220/230/240V or 480/400/415V

SYA8K16I

### Overview

<b>Presentation</b>	High performance, redundant power protection with scalable power and runtime for space-constrained server rooms, and voice and data networks.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	230 V 400 V 3 phases
<b>Other Input Voltage</b>	220 V 240 V 380 V 415 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated power in W</b>	5600 W
<b>Rated power in VA</b>	8000 VA
<b>Output connector type</b>	Hard wire 3-wire (H N + E) 1
<b>Battery type</b>	Lead-acid battery
<b>Provided equipment</b>	CD with software Documentation CD Installation guide User manual Web/SNMP management card

### Batteries & Runtime

<b>Number of battery filled slots</b>	2
<b>Number of battery free slots</b>	2
<b>Battery recharge time</b>	3 h
<b>Additional information</b>	Configurable for 220 : 230 or 240 nominal output voltage
<b>Battery charger power</b>	574 W rated
<b>Battery power in VAh</b>	1728 VAh runtime
<b>Battery life</b>	3...5 year(s)
<b>Replacement battery</b>	<a href="#">SYBT5</a>
<b>Battery option</b>	SYBT5 1 2592 VAh SYBT5 2 3456 VAh SYAXR9B9I 1 9504 VAh SYAXR9B9I 2 17280 VAh

SYAXR9B9I 3 25056 VAh  
SYAXR9B9I 4 32832 VAh  
SYAXR9B9I 5 40608 VAh  
SYAXR9B9I 6 48384 VAh

---

Extended runtime	1
------------------	---

## General

---

Product web sub-family	4kVA power increments
------------------------	-----------------------

---

Number of power module free slots	3
-----------------------------------	---

---

Number of power module filled slots	2
-------------------------------------	---

---

Redundant	Yes
-----------	-----

## Physical

---

Colour	Black Silver
--------	-----------------

---

Height	93.7 cm
--------	---------

---

Width	48.3 cm
-------	---------

---

Depth	72.6 cm
-------	---------

---

Net weight	219.55 kg
------------	-----------

---

Mounting location	Front
-------------------	-------

---

Mounting preference	No preference
---------------------	---------------

---

Mounting mode	Not rack-mountable
---------------	--------------------

---

Two post mountable	0
--------------------	---

---

USB compatible	No
----------------	----

## Input

---

Network frequency	45...65 Hz auto-sensing
-------------------	-------------------------

---

Number of input connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E)
----------------------------	--

---

Input voltage limits	155...276 V 290...480 V 3:1
----------------------	--------------------------------

---

Input harmonic distortion	Less than 7 % for full load
---------------------------	-----------------------------

---

Input Power Factor at Full Load	0.98
---------------------------------	------

## Output

---

Maximum configurable power in W	11200 W
---------------------------------	---------

---

Harmonic distortion	Less than 5 % at full load
---------------------	----------------------------

---

Output frequency	47...63 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
------------------	--

---

Crest factor	Up to 5 : 1
--------------	-------------

---

UPS type	Double conversion online
----------	--------------------------

---

Wave type	Sine wave
-----------	-----------

---

Bypass type	Internal bypass (automatic and manual)
-------------	--

---

Maximum output current	36 A
------------------------	------

---

Maximum configurable power in VA	16000 VA
----------------------------------	----------

## Conformance

Product certifications	C-Tick CE GOST VDE
Standards	EN 50091-1 EN 50091-2 EN 55022 class A EN 55024 EN 60950 IEC 60950

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...4572.00 m
Acoustic level	62 dBA
Heat dissipation	3707 Btu/h

## Communications & Management

Free slots	1
Preinstalled device	Network management card 2 with environmental monitoring
Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	118.1 cm
Package 1 Width	99.7 cm
Package 1 Length	59.9 cm
Package 1 Weight	236.82 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

---

Warranty 2 years repair or replace

Recommended replacement(s)